

Interior / Exterior 100% Acrylic Block Filler  
Architectural Coating - Premium Plus

### Description

A premium plus 100% acrylic heavy-duty interior / exterior block filler designed to fill pores and small voids in CMU (concrete masonry units) without shrinking or cracking. Provides excellent filling, holdout and foundation for a wide variety of conventional topcoats including epoxy coatings. The products 100% acrylic composition will provide better efflorescence and alkalininity properties.

### Recommended Uses

A heavy-duty block filler for concrete block masonry surfaces to receive a paint or coatings finish.

### Limitations

This filler is not recommended for use as a waterproofer or on free standing, retaining and below-grade masonry walls. Avoid using on surfaces exposed to severe moisture or hydrostatic pressure.

### Colors

White

### Packaging

Five gallon containers

### Finish

Flat with slight angular sheen, sheen @ 85° = 2.5 – 3.5%

### Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings.

### Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Light overspray can be cleaned up with water even after drying. Clean tools and equipment with soap and water.

### Drying Time

Touch: 2 hours

Recoat: 8 hours

### Coverage

Up to 70 square feet per gallon, depending on porosity and texture of the surface. Apply to a flush fill, free of pinholes.

### Mil Thickness

Wet = 18.0 - 22.0

Dry = 9.0 - 11.0

### Thinning

Use at package consistency. If thinning is required, use water sparingly.

### Composition

Titanium Dioxide	7.5%
Extenders	30.1%
<b>TOTAL PIGMENT</b>	<b>37.6%</b>

Acrylic Resin	22.7%
Additives	5.9%
Water	33.8%
<b>TOTAL VEHICLE</b>	<b>62.4%</b>

Weights & Measurements +/-3.0%

Solids by Volume:	48.0%
Solids by Weight:	73.0%
VOC:	23 g/l
Weight Per Gal:	11.4 lbs.
Viscosity:	110 - 116 KU

### Conformance

**SCAQMD** - complies with Rule 1113, Architectural Coatings.

**CDPH Section 01350** - tested and passed



Products bearing this logo are Non-EG Certified. Ethylene Glycol (EG), is listed as a toxic air contaminant and hazardous pollutant. EG is a solvent used in some water-based paints. Vista Paint has replaced EG with non-toxic alternative solvents. Any Vista Paint product with this logo is formulated without EG (Non-EG).



Vista Paint is the industry leader when it comes to relying on renewable energy. At Vista Paint, our products are manufactured using 100% solar energy.

12.2023

**DISCLAIMER:** To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.