

Interior / Exterior Acrylic Block Filler Architectural Coating - Premium

040 Block Kote Interior / Exterior Acrylic Block Filler

Description

A premium acrylic interior and exterior heavy-bodied block filler designed to fill voids in concrete, block, masonry and brick without shrinking or cracking. Compatible with alkylid and acrylic topcoats.

Recommended Uses

New or previously painted concrete, block, masonry and brick.

Colors

White

Packaging

Five gallon containers

Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings.

Primer

Masonry / Concrete / Block: 4600 Uniprime II

Application

Brush, roll or spray. If sprayed, follow immediately with a paint roller to work the material into the surface. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

Drying Time

Touch: 2 hours
Recoat: 8 hours

Coverage

Up to 250 square feet per gallon, depending on porosity and texture of the surface.

Mil Thickness

Depending on Porosity
Wet = 6.0 - 22.0 Dry = 3.0 - 10.0

Thinning

Use at package consistency. If thinning is required, use water sparingly.

Composition

Titanium Dioxide	7.1%
Extenders	41.6%
TOTAL PIGMENT	48.7%
Vinyl Acrylic Resin	12.6%
Additives	7.2%
Water	31.5%
TOTAL VEHICLE	51.3%

Weights & Measurements +/-3.0%

Solids by Volume:	50.3%
Solids by Weight:	66.3%
VOC:	23 g/l
Weight Per Gal:	12.3 lbs.
Viscosity:	105 - 115 KU

Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings.

CDPH Section 01350 - Standard Method V1.2 2017

MPI - #4



Products bearing this logo are Non-EG Certified. Ethylene Glycol (EG), is listed as a toxic air contaminant and hazardous pollutant. EG is a solvent used in some water-based paints. Vista Paint has replaced EG with non-toxic alternative solvents. Any Vista Paint product with this logo is formulated without EG (Non-EG).



Vista Paint is the industry leader when it comes to relying on renewable energy. At Vista Paint, our products are manufactured using 100% solar energy.

Updated 02.2024

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

