

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name HI-BUILD SEALER

Product Code .1100

Product Class WATER THINNED PAINT

Recommended use Paint

Restrictions on use No information available

Manufacturer

Vista Paint Corporation 2020 E. Orangethorpe Ave. Fullerton, CA 92831

(714) 680-3800

Emergency Telephone Number(s): (800) 535-5053 (Infotrac)

# 2. HAZARD(S) IDENTIFICATION





**GHS Pictograms:** 

Signal Word: Danger

GHS Classifications: Eye Irritation Category 2A

Skin Irritation Category 2
Carcinogenicity Category 1A

**Hazard Statements:** H319 – Causes serious eye irritation

H315 – Causes skin irritation

**H350i** – May cause cancer by inhalation

**Precautionary Statements:** 

**Prevention** 

P103 - Read label before use.

**P201 –** Obtain special instructions before use.

**P202** – Do not handle until all safety precautions have been read and understood.

**P261 –** Avoid breathing dust/fume/gas/mist/vapors/spray.

**P264** – Wash hands thoroughly after handling. **P273** – Avoid release to the environment.

P273 - Avoid release to the environment.

**P280 –** Wear protective gloves / eye protection / face protection. **P285 –** In case of inadequate ventilation wear respiratory protection.

Response

P301 + P310 - If swallowed: Immediately call a poison center or

doctor/physician.

**P308 + P313 –** If exposed or concerned: Get medical advice/attention.

Page 1 of 7

P320 + P352 - If on skin: Wash with plenty of water

Product Name: HI-BUILD SEALER Vista Paint Corporation

P332 + P313 - If skin irritation occurs: Get medical advice/attention.
 P362 + P364 - Take off contaminated clothing and wash it before reuse.
 P305 + P351 + P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lens, if present and easy to do.

Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical advice/attention

<u>Storage</u>

P405 - Store locked up.

**Disposal** 

P501 – Dispose of contents/container in accordance with local/state/federal

regulations.

HNOC: Not Applicable

Other information: No Information Available

## 3. COMPOSITION INFORMATION ON COMPONENTS

<u>Hazardous Component</u> <u>CAS Number</u>		<u>Weight %</u>		
Titanium Dioxide	13463-67-7	13.04		
Limestone	1317-65-3	6.77		
Quartz (SiO2)	14808-60-7	0.60		

## 4. FIRST AID MEASURES

**General Advice:** No hazards which require special first aid measures.

Eye Contact: Rinse thoroughly with plenty of water for at least 15 minutes and

consult a physician.

**Skin Contact:** Wash off immediately with soap and plenty of water removing all contaminated

clothes and shoes.

**Inhalation:** Move to fresh air. If symptoms persist, call a physician.

Ingestion: Clean mouth with water and afterwards drink plenty of water. Consult a

physician if necessary.

Most Important Symptoms/Effects: None known.

Notes To Physician: Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Use extinguishing measures that are appropriate to local circumstances and

the surrounding environment.

**Protective Equipment And**As in any fire, wear self-contained breathing apparatus pressure-demand,

Page 2 of 7

Precautions For Firefighters: MSHA/NIOSH (approved or equivalent) and full protective gear.

Product Name: HI-BUILD SEALER Vista Paint Corporation

Specific Hazards Arising From The Chemical:

Closed containers may rupture if exposed to fire or extreme heat

### **6. ACCIDENTAL RELEASE MEASURES**

**Personal Precautions:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

**Other Information:** Prevent further leakage or spillage if safe to do so.

**Environmental Precautions:** See Section 12 for additional Ecological Information.

**Methods For Clean-Up:** Soak up with inert absorbent material. Sweep up and shovel into suitable

containers for disposal.

## 7. HANDLING AND STORAGE

Handling: Avoid breathing vapors, spray

mists or sanding dust. In case of insufficient ventilation, wear suitable

respiratory equipment.

Storage: Keep container tightly closed. Keep out of the reach of children. Keep from

freezing.

Incompatible Materials: No information available

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits			AGCIH	(	OSHA Exposure Limits		its	
REPORTABLE COMPONENTS	CAS NUMBER	% <b>W</b> T	LV/TWA PPM		NA MG/M3		EL MG/M3	Vapor Pressure mm Hg @20° C
Titanium Dioxide	13463-67-7	13.04	10	-	10	-	-	-
Limestone	1317-65-3	6.77	-	-	15	-	-	-
Quartz (SiO2)	14808-60-7	0.60	-	-	0.05	-	-	-

**Eye/Face Protection:** Safety glasses with side-shields.

**Skin Protection** Protective gloves and impervious clothing.

**Respiratory Protection** In case of insufficient ventilation wear suitable respiratory equipment. When

sanding or abrading the dried paint film, wear a dust / mist respirator approved

by NIOSH/MSHA for dust which may be generated from this product,

underlying paint, or the abrasive material itself.

**Engineering Measures:** Ensure adequate ventilation, especially in confined areas.

Product Code: .1100

Product Name: HI-BUILD SEALER

**Vista Paint Corporation** 

Page 3 of 7

**Hygiene Measures:** 

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Liquid

**Odor** Little or no odor

Odor Threshold

pH

No information available

No information available

Freezing Point (°F) 32 °F Boiling Point (°F) 212 °F

Flash Point (°F)

Flash Point Method

Not applicable
Not applicable

**Evaporation Rate**No information available

Flammability (solid, gas)
Upper Explosion Limit
Lower Explosion Limit
Not applicable
Not applicable

Vapor PressureNo information availableVapor DensityNo information available

Density (lbs./gal) 10.69 Specific Gravity 1.28

Solubility
Water Solubility
Partition Coefficient (n-octanol/water)
Autoignition Temperature (°F)
Decomposition Temperature (°F)
Viscosity (cps)
No information available
No information available
No information available
No information available

 Wt. % Solids
 50.97

 Vol. % Solids
 37.06

 Wt. % Volatiles
 49.03

 Vol. % Volatiles
 62.94

 Coating VOC
 94.06 g/l

 Material VOC
 38.46 g/l

## 10. STABILITY AND REACTIVITY

Reactivity Not Applicable

Chemical Stability Stable under normal conditions.

Possibility Of Hazardous Reactions None under normal conditions of use.

Conditions To Avoid Prevent from freezing

Incompatible Materials No materials to be especially mentioned.

Hazardous Decomposition Products

None under normal use.

#### 11. TOXICOLOGICAL INFORMATION

Principal Routes of Exposure: Eye contact, skin contact and inhalation.

Acute Toxicity: No information available

Product Name: HI-BUILD SEALER Vista Paint Corporation Page 4 of 7

Symptoms No information available

**Eye contact** May cause slight irritation.

Skin contact Substance may cause slight skin irritation. Prolonged or

repeated contact may dry skin and cause irritation.

**Inhalation** May cause irritation of respiratory tract.

**Ingestion** Ingestion may cause gastrointestinal irritation, nausea,

vomiting and diarrhea.

Sensitization: No information available

Neurological Effects No information available.

Mutagenic Effects No information available.

**Reproductive Effects**No information available.

**Developmental Effects**No information available.

Target Organ Effects No information available.

**STOT - single exposure**No information available.

STOT - repeated exposure No information available.

Other adverse effects No information available.

Aspiration Hazard No information available

#### Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen:.

Chemical Name	IARC	NTP	OSHA Carcinogen	
Titanium Dioxide	2B - Possible Human			
Titanium bioxide	Carcinogen			
Crystallina Ciliaa Dasnirahla	1 – Carcinogenic to	Known Carsingson	Listed	
Crystalline Silica, Respirable	Humans	Known Carcinogen		

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

#### Legend

IARC - International Agency for Research on Cancer NTP - National Toxicity Program OSHA - Occupational Safety & Health Administration

## 12. ECOLOGICAL INFORMATION

Product Name: HI-BUILD SEALER Vista Paint Corporation Page 5 of 7

**Ecotoxicity Effects**The environmental impact of this product has not been fully

investigated.

Acute Toxicity to Fish (Titanium Dioxide) LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

Acute Toxicity to Aquatic Invertebrates No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available

Bioaccumulation / Accumulation No information available

Mobility in Environmental Media No information available

Ozone No information available

#### 13. DISPOSAL CONSIDERATIONS

**Waste Disposal Method** Dispose of in accordance with federal, state, provincial, and local regulations.

Local requirements may vary, consult your sanitation department or

state-designated environmental protection agency for more disposal options.

#### 14. TRANSPORT INFORMATION

**DOT** Not regulated

ICAO / IATA Not regulated

IMDG / IMO Not regulated

### 15. REGULATORY INFORMATION

### **International Inventories**

**TSCA: United States**Yes - All components are listed or exempt.

Yes - All components are listed or exempt.

### Federal Regulations

#### SARA 311/312 hazardous categorization

Please refer to Section 2 of the SDS for the appropriate EPCRA 311/312 hazard categories.

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). If listed in the table below, this product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

<u>Chemical Name</u> <u>CAS Number</u>

None None

Product Name: HI-BUILD SEALER Vista Paint Corporation Page 6 of 7

#### Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

Unless listed below, this product does not contain HAPs at 1% or 0.1% or greater. Refer to Section 3 for HAP weight percentage:

<u>Chemical Name</u> <u>CAS Number</u>

None Nor

### **State Regulations**

#### **California Proposition 65**

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm at levels less than required for reporting (<0.1%) unless listed in Section 3.

#### **16. OTHER INFORMATION**

HMIS Health: 1\* Flammability: 0 Reactivity: 0 PPE: X

NFPA: Health: 1 Flammability: 0 Instability: 0

Prepared By Vista Paint Corporation

2020 East Orangethorpe Avenue

Fullerton, CA 92831 (714) 680-3800

**Print Date:** 07/05/2023

Revision Date: 05/23/2023

**Revision Summary:** Formulation change

### Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

Form Date: 2020-01-22

**END OF SAFETY DATA SHEET** 

Product Name: HI-BUILD SEALER Vista Paint Corporation Page 7 of 7