

Interior Water-Based Pigmented PVA Sealer Architectural Coating - Quality

Description

A water-based pigmented PVA sealer for interior use on drywall and plaster. Seals the substrate providing a good foundation and enamel hold-out for various topcoats.

Recommended Uses

New interior drywall and plaster.

Colors

White and #158 Shell White

Packaging

Five gallon containers

Finish

Flat

Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application. Not recommended for use over previously painted surfaces.

Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

Drying Time

Touch: 30 minutes
Recoat: 2 hours

Coverage

250 - 400 square feet per gallon, depending on porosity and texture of the surface.

Mil Thickness

Wet = 3.7 Dry = 1.2

Thinning

Use at package consistency. If thinning is required, use water sparingly.

Composition

Titanium Dioxide	7.2%
Extenders	18.5%
TOTAL PIGMENT	25.7%
Resin	17.3%
Additives	8.9%
Water	48.7%
TOTAL VEHICLE	74.9%

Weights & Measurements +/-3.0%

Solids by Volume:	32.4%
Solids by Weight:	43.9%
VOC:	94 g/l
Weight Per Gal:	10.3 lbs.
Viscosity:	94 - 98 KU

Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings.

Proprietary Substitute for TT-P-650



Products bearing this logo are Non-EG Certified. Ethylene Glycol (EG), is listed as a toxic air contaminant and hazardous pollutant. EG is a solvent used in some water-based paints. Vista Paint has replaced EG with non-toxic alternative solvents. Any Vista Paint product with this logo is formulated without EG (Non-EG).



Vista Paint is the industry leader when it comes to relying on renewable energy. At Vista Paint, our products are manufactured using 100% solar energy.

12.2023

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

