

  
**SAFETY DATA SHEET**

**1. PRODUCT AND COMPANY IDENTIFICATION**

**Product Name** GREEN BIKETRAC KOTE PARTS A+B  
**Product Code** .455  
**Product Class** WATER THINNED PAINT  
**Recommended use** Paint  
**Restrictions on use** No information available

**Manufacturer**  
Vista Paint Corporation  
2020 E. Orangethorpe Ave.  
Fullerton, CA 92831  
(714) 680-3800

**Emergency Telephone Number(s):** (800) 535-5053 (Infotrac)

**2. HAZARD(S) IDENTIFICATION**



**GHS Pictograms:**

**Signal Word:** Danger

**GHS Classifications:**

Eye Irritation	Category 2A
Skin Irritation	Category 2
Carcinogenicity	Category 1A

**Hazard Statements:**

H319 – Causes serious eye irritation  
H315 – Causes skin irritation  
H350i – May cause cancer by inhalation

**Precautionary Statements:**

**Prevention**

**P103** – Read label before use.  
**P201** – Obtain special instructions before use.  
**P202** – Do not handle until all safety precautions have been read and understood.  
**P261** – Avoid breathing dust/fume/gas/mist/vapors/spray.  
**P264** – Wash hands thoroughly after handling.  
**P273** – Avoid release to the environment.  
**P280** – Wear protective gloves / eye protection / face protection.  
**P285** – In case of inadequate ventilation wear respiratory protection.

**Response**

**P301 + P310** – If swallowed: Immediately call a poison center or doctor/physician.  
**P308 + P313** – If exposed or concerned: Get medical advice/attention.  
**P320 + P352** – If on skin: Wash with plenty of water

**P332 + P313** – If skin irritation occurs: Get medical advice/attention.  
**P362 + P364** – Take off contaminated clothing and wash it before reuse.  
**P305 + P351 + P338** – If in eyes: Rinse cautiously with water for several minutes. Remove contact lens, if present and easy to do. Continue rinsing.  
**P337 + P313** – If eye irritation persists: Get medical advice/attention

**Storage**

**P405** – Store locked up.

**Disposal**

**P501** – Dispose of contents/container in accordance with local/state/federal regulations.

**HNOC:** Not Applicable

**Other information:** No Information Available

**3. COMPOSITION INFORMATION ON COMPONENTS**

<u>Hazardous Component</u>	<u>CAS Number</u>	<u>Weight %</u>
Limestone	1317-65-3	59.13
Ethyl Alcohol	64-17-5	1.45
BIS PHENOL A EPOXY RESIN	25085-99-8	1.34
Quartz (SiO2)	14808-60-7	0.30

**4. FIRST AID MEASURES**

**General Advice:** No hazards which require special first aid measures.

**Eye Contact:** Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

**Skin Contact:** Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes.

**Inhalation:** Move to fresh air. If symptoms persist, call a physician.

**Ingestion:** Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.

**Most Important Symptoms/Effects:** None known.

**Notes To Physician:** Treat symptomatically.

**5. FIRE-FIGHTING MEASURES**

**Suitable Extinguishing Media:** Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Protective Equipment And Precautions For Firefighters:**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**Specific Hazards Arising From The Chemical:**

Closed containers may rupture if exposed to fire or extreme heat

**6. ACCIDENTAL RELEASE MEASURES**

**Personal Precautions:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

**Other Information:** Prevent further leakage or spillage if safe to do so.

**Environmental Precautions:** See Section 12 for additional Ecological Information.

**Methods For Clean-Up:** Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

**7. HANDLING AND STORAGE**

**Handling:** Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

**Storage:** Keep container tightly closed. Keep out of the reach of children. Keep from freezing.

**Incompatible Materials:** No information available

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Exposure Limits**

REPORTABLE COMPONENTS	CAS NUMBER	%WT	OSHA Exposure Limits				Vapor Pressure mm Hg @20° C	
			AGCIH LV/TWA PPM	PPM	TWA MG/M3	STEL PPM		
Limestone	1317-65-3	59.13	-	-	15	-	-	-
Ethyl Alcohol	64-17-5	1.45	-	1000	1900	-	-	-
BIS PHENOL A EPOXY RESIN	25085-99-8	1.34	-	-	-	-	-	-
Quartz (SiO2)	14808-60-7	0.30	-	-	0.05	-	-	-

**Eye/Face Protection:** Safety glasses with side-shields.

**Skin Protection** Protective gloves and impervious clothing.

**Respiratory Protection** In case of insufficient ventilation wear suitable respiratory equipment. When sanding or abrading the dried paint film, wear a dust / mist respirator approved

by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive material itself.

**Engineering Measures:** Ensure adequate ventilation, especially in confined areas.

**Hygiene Measures:** Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid
Odor	Little or no odor
Odor Threshold	No information available
pH	No information available
Freezing Point (°F)	32 °F
Boiling Point (°F)	212 °F
Flash Point (°F)	Not applicable
Flash Point Method	Not applicable
Evaporation Rate	No information available
Flammability (solid, gas)	Not applicable
Upper Explosion Limit	Not applicable
Lower Explosion Limit	Not applicable
Vapor Pressure	No information available
Vapor Density	No information available
Density (lbs./gal)	13.84
Specific Gravity	1.66
Solubility	No information available
Water Solubility	No information available
Partition Coefficient (n-octanol/water)	No information available
Autoignition Temperature (°F)	No information available
Decomposition Temperature (°F)	No information available
Viscosity (cps)	No information available
Wt. % Solids	78.61
Vol. % Solids	63.62
Wt. % Volatiles	21.39
Vol. % Volatiles	36.38
Coating VOC	75.90 g/l
Material VOC	52.86 g/l

## 10. STABILITY AND REACTIVITY

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions.
Possibility Of Hazardous Reactions	None under normal conditions of use.
Conditions To Avoid	Prevent from freezing
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	None under normal use.

## 11. TOXICOLOGICAL INFORMATION

<b>Principal Routes of Exposure:</b>	Eye contact, skin contact and inhalation.
<b>Acute Toxicity:</b>	No information available
<b>Symptoms</b>	No information available
<b>Eye contact</b>	May cause slight irritation.
<b>Skin contact</b>	Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation.
<b>Inhalation</b>	May cause irritation of respiratory tract.
<b>Ingestion</b>	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
<b>Sensitization:</b>	No information available
<b>Neurological Effects</b>	No information available.
<b>Mutagenic Effects</b>	No information available.
<b>Reproductive Effects</b>	No information available.
<b>Developmental Effects</b>	No information available.
<b>Target Organ Effects</b>	No information available.
<b>STOT - single exposure</b>	No information available.
<b>STOT - repeated exposure</b>	No information available.
<b>Other adverse effects</b>	No information available.
<b>Aspiration Hazard</b>	No information available

### Carcinogenicity

*The information below indicates whether each agency has listed any ingredient as a carcinogen.*

Chemical Name	IARC	NTP	OSHA Carcinogen
Titanium Dioxide	2B - Possible Human Carcinogen		
Crystalline Silica, Respirable	1 - Carcinogenic to Humans	Known Carcinogen	Listed

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

### Legend

IARC - International Agency for Research on Cancer

Product Name: GREEN BIKETRAC KOTE PARTS A+B  
of 7

Vista Paint Corporation

Page 5

Product Code: .455

## 12. ECOLOGICAL INFORMATION

<b><u>Ecotoxicity Effects</u></b>	The environmental impact of this product has not been fully investigated.
<b>Acute Toxicity to Fish (Titanium Dioxide)</b>	LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)
<b>Acute Toxicity to Aquatic Invertebrates</b>	No information available
<b>Acute Toxicity to Aquatic Plants</b>	No information available
<b>Persistence / Degradability</b>	No information available
<b>Bioaccumulation / Accumulation</b>	No information available
<b>Mobility in Environmental Media</b>	No information available
<b>Ozone</b>	No information available

## 13. DISPOSAL CONSIDERATIONS

<b>Waste Disposal Method</b>	Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.
------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

## 14. TRANSPORT INFORMATION

<b>DOT</b>	Not regulated
<b>ICAO / IATA</b>	Not regulated
<b>IMDG / IMO</b>	Not regulated

## 15. REGULATORY INFORMATION

### **International Inventories**

<b>TSCA: United States</b>	Yes - All components are listed or exempt.
<b>DSL: Canada</b>	Yes - All components are listed or exempt.

### **Federal Regulations**

#### **SARA 311/312 hazardous categorization**

Please refer to Section 2 of the SDS for the appropriate EPCRA 311/312 hazard categories.

