


SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name UNIPRIME II
Product Code .4600
Product Class WATER THINNED PAINT
Recommended use Paint
Restrictions on use No information available

Manufacturer
Vista Paint Corporation
2020 E. Orangethorpe Ave.
Fullerton, CA 92831
(714) 680-3800

Emergency Telephone Number(s): (800) 535-5053 (Infotrac)

2. HAZARD(S) IDENTIFICATION



GHS Pictograms:

Signal Word: Danger

GHS Classifications:

Eye Irritation	Category 2A
Skin Irritation	Category 2
Carcinogenicity	Category 1A

Hazard Statements:

H319 – Causes serious eye irritation
H315 – Causes skin irritation
H350i – May cause cancer by inhalation

Precautionary Statements:

Prevention

P103 – Read label before use.
P201 – Obtain special instructions before use.
P202 – Do not handle until all safety precautions have been read and understood.
P261 – Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 – Wash hands thoroughly after handling.
P273 – Avoid release to the environment.
P280 – Wear protective gloves / eye protection / face protection.
P285 – In case of inadequate ventilation wear respiratory protection.

Response

P301 + P310 – If swallowed: Immediately call a poison center or doctor/physician.
P308 + P313 – If exposed or concerned: Get medical advice/attention.
P320 + P352 – If on skin: Wash with plenty of water

P332 + P313 – If skin irritation occurs: Get medical advice/attention.
P362 + P364 – Take off contaminated clothing and wash it before reuse.
P305 + P351 + P338 – If in eyes: Rinse cautiously with water for several minutes. Remove contact lens, if present and easy to do. Continue rinsing.
P337 + P313 – If eye irritation persists: Get medical advice/attention

Storage

P405 – Store locked up.

Disposal

P501 – Dispose of contents/container in accordance with local/state/federal regulations.

HNOC: Not Applicable

Other information: No Information Available

3. COMPOSITION INFORMATION ON COMPONENTS

<u>Hazardous Component</u>	<u>CAS Number</u>	<u>Weight %</u>
Limestone	1317-65-3	14.00
Titanium Dioxide	13463-67-7	11.66
Talc	14807-96-6	2.26

4. FIRST AID MEASURES

General Advice: No hazards which require special first aid measures.

Eye Contact: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

Skin Contact: Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes.

Inhalation: Move to fresh air. If symptoms persist, call a physician.

Ingestion: Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.

Most Important Symptoms/Effects: None known.

Notes To Physician: Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Protective Equipment And Precautions For Firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Specific Hazards Arising From The Chemical:

Closed containers may rupture if exposed to fire or extreme heat

6. ACCIDENTAL RELEASE MEASURES

- Personal Precautions:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.
- Other Information:** Prevent further leakage or spillage if safe to do so.
- Environmental Precautions:** See Section 12 for additional Ecological Information.
- Methods For Clean-Up:** Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

7. HANDLING AND STORAGE

- Handling:** Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.
- Storage:** Keep container tightly closed. Keep out of the reach of children. Keep from freezing.
- Incompatible Materials:** No information available

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits

REPORTABLE COMPONENTS	CAS NUMBER	%WT	OSHA Exposure Limits					Vapor Pressure mm Hg @20° C
			AGCIH LV/TWA PPM	TWA PPM	MG/M3	STEL PPM	MG/M3	
Limestone	1317-65-3	14.00	-	-	15	-	-	-
Titanium Dioxide	13463-67-7	11.66	10	-	10	-	-	-
Talc	14807-96-6	2.26	-	-	2	-	-	-

- Eye/Face Protection:** Safety glasses with side-shields.
- Skin Protection** Protective gloves and impervious clothing.
- Respiratory Protection** In case of insufficient ventilation wear suitable respiratory equipment. When sanding or abrading the dried paint film, wear a dust / mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive material itself.
- Engineering Measures:** Ensure adequate ventilation, especially in confined areas.

Hygiene Measures:

Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid
Odor	Little or no odor
Odor Threshold	No information available
pH	No information available
Freezing Point (°F)	32 °F
Boiling Point (°F)	212 °F
Flash Point (°F)	Not applicable
Flash Point Method	Not applicable
Evaporation Rate	No information available
Flammability (solid, gas)	Not applicable
Upper Explosion Limit	Not applicable
Lower Explosion Limit	Not applicable
Vapor Pressure	No information available
Vapor Density	No information available
Density (lbs./gal)	10.60
Specific Gravity	1.27
Solubility	No information available
Water Solubility	No information available
Partition Coefficient (n-octanol/water)	No information available
Autoignition Temperature (°F)	No information available
Decomposition Temperature (°F)	No information available
Viscosity (cps)	No information available
Wt. % Solids	51.03
Vol. % Solids	37.74
Wt. % Volatiles	48.97
Vol. % Volatiles	62.26
Coating VOC	36.02 g/l
Material VOC	14.12 g/l

10. STABILITY AND REACTIVITY

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions.
Possibility Of Hazardous Reactions	None under normal conditions of use.
Conditions To Avoid	Prevent from freezing
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	None under normal use.

11. TOXICOLOGICAL INFORMATION

Principal Routes of Exposure: Eye contact, skin contact and inhalation.

Acute Toxicity: No information available

Symptoms	No information available
Eye contact	May cause slight irritation.
Skin contact	Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation.
Inhalation	May cause irritation of respiratory tract.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Sensitization:	No information available
Neurological Effects	No information available.
Mutagenic Effects	No information available.
Reproductive Effects	No information available.
Developmental Effects	No information available.
Target Organ Effects	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Other adverse effects	No information available.
Aspiration Hazard	No information available

Carcinogenicity

The information below indicates whether each agency has listed any ingredient as a carcinogen.:

Chemical Name	IARC	NTP	OSHA Carcinogen
Titanium Dioxide	2B - Possible Human Carcinogen		
Crystalline Silica, Respirable	1 – Carcinogenic to Humans	Known Carcinogen	Listed

• Although IARC has classified titanium dioxide as possibly carcinogenic to humans (2B), their summary concludes: "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as paint."

Legend

IARC - International Agency for Research on Cancer

NTP - National Toxicity Program

OSHA - Occupational Safety & Health Administration

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects

The environmental impact of this product has not been fully investigated.

Acute Toxicity to Fish (Titanium Dioxide)

LC50: > 1000 mg/L (Fathead Minnow - 96 hr.)

Acute Toxicity to Aquatic Invertebrates

No information available

Acute Toxicity to Aquatic Plants

No information available

Persistence / Degradability

No information available

Bioaccumulation / Accumulation

No information available

Mobility in Environmental Media

No information available

Ozone

No information available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

14. TRANSPORT INFORMATION

DOT

Not regulated

ICAO / IATA

Not regulated

IMDG / IMO

Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA: United States

Yes - All components are listed or exempt.

DSL: Canada

Yes - All components are listed or exempt.

Federal Regulations

SARA 311/312 hazardous categorization

Please refer to Section 2 of the SDS for the appropriate EPCRA 311/312 hazard categories.

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). If listed in the table below, this product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name

None

CAS Number

None

Product Name: UNIPRIME II

Vista Paint Corporation

Page 6 of 7

Product Code: .4600

