

Zero\* V.O.C., Low Odor Interior Latex Primer  
Architectural Coating - Premium

### Description

V-PRO 5000 Primer (5001) is a zero\* VOC, interior quality latex primer for use on new drywall, masonry, concrete and acoustic surfaces. This product creates an even surface porosity that provides a good foundation for finish coats.

**NOTE:** This product contains ingredients which resist the growth of microbes on the surface of the paint film.

### Recommended Uses

Designed for commercial and institutional projects on new interior drywall, plaster, masonry, concrete, block, tilt-ups and acoustic surfaces.

### Colors

White

### Packaging

One and five gallon containers

### Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. NOT recommended for use over previously painted surfaces. On previously painted surfaces Vista No. 4000 Uniprime is recommended.

### Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Light overspray can be cleaned up with water even after drying. Clean tools and equipment with soap and water.

### Drying Time

Touch: 45 minutes  
Recoat: 2 hours

### Coverage

Up to 425 square feet per gallon, depending on porosity and texture of the surface.

### Mil Thickness

Wet = 3.7      Dry = 1.2

### Thinning

Use at package consistency. If thinning is required, use water sparingly.

### Composition

Titanium Dioxide	9.3%
Extenders	13.2%
<b>TOTAL PIGMENT</b>	<b>22.5%</b>

Latex Resin	17.6%
Additives	7.1%
Water	52.8%
<b>TOTAL VEHICLE</b>	<b>77.5%</b>

Weights & Measurements +/-3.0%

Solids by Volume:	33.2%
Solids by Weight:	43.9%
VOC:	<3 g/l
Weight Per Gal:	9.98 lbs.
Viscosity:	90 - 94 KU

### Conformance

**SCAQMD** - complies with Rule 1113, Architectural Coatings.

**LEED** - complies with LEEDv4

**CDPH Section 01350** - Standard Method V1.2 2017

**MPI** - #50, #149

\*NOTE: Zero VOC is defined as no VOC containing solvents added in the manufacturing process of this product. Slight traces of VOC are present in additives used in manufacturing. This product has less than half the allowable VOC of the SCAQMD Super Compliant Coatings category.

\*NOTE: This product complies with the Super Compliant Coatings category under SCAQMD definitions.



Products bearing this logo are Non-EG Certified. Ethylene Glycol (EG), is listed as a toxic air contaminant and hazardous pollutant. EG is a solvent used in some water-based paints. Vista Paint has replaced EG with non-toxic alternative solvents. Any Vista Paint product with this logo is formulated without EG (Non-EG).



Vista Paint is the industry leader when it comes to relying on renewable energy. At Vista Paint, our products are manufactured using 100% solar energy.

12.2023

**DISCLAIMER:** To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

