

### **1. PRODUCT AND COMPANY IDENTIFICATION**

Product Name Product Code Product Class Recommended use Restrictions on use V-PRO 5000 FLAT .5100 WATER THINNED PAINT Paint No information available

Manufacturer Vista Paint Corporation 2020 E. Orangethorpe Ave. Fullerton, CA 92831 (714) 680-3800

Emergency Telephone Number(s): (800) 535-5053 (Infotrac)

2. HAZARD(S) IDENTIFICATION		
GHS Pictograms:	(!)	
Signal Word:	Warning	
GHS Classifications:	Eye Irritation Skin Irritation	Category 2A Category 2
Hazard Statements:	H319 - Causes seriou H315 – Causes skin i	
Precautionary Statements:	P264 – Wash hands th	g dust/fume/gas/mist/vapors/spray. oroughly after handling.
		e gloves / eye protection / face protection. equate ventilation wear respiratory protection.
		ALLOWED: Immediately call a POISON CENTER or /physician.
		in: Wash with plenty of water
		irritation occurs: Get medical advice/attention.
	- P305 + P351 + P338 minute	<ul> <li>ff contaminated clothing and wash it before reuse.</li> <li>IF IN EYES: Rinse cautiously with water for several es. Remove contact lenses, if present and easy to do. nue rinsing.</li> </ul>
		rritation persists: Get medical advice/attention

### <u>Disposal</u>

**P501 –** Dispose of contents/container in accordance with local/state/federal regulations.

HNOC:	Not Applicable

Other information:

No information available

# 3. COMPOSITION INFORMATION ON COMPONENTS

Hazardous Component	CAS Number	<u>Weight %</u>
Limestone	1317-65-3	16.23
Titanium Dioxide	13463-67-7	11.70

# 4. FIRST AID MEASURES

General Advice:	No hazards which require special first aid measures.
Eye Contact:	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Skin Contact:	Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes.
Inhalation:	Move to fresh air. If symptoms persist, call a physician.
Ingestion:	Clean mouth with water and afterwards drink plenty of water. Consult a physician if necessary.
Most Important Symptoms/Effects:	None known.
Notes To Physician:	Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Protective Equipment And Precautions For Firefighters:	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Specific Hazards Arising From The Chemical:	Closed containers may rupture if exposed to fire or extreme heat

# 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.		
Other Information:	Prevent further leakage or spillage if safe to do so.		
Environmental Precautions:	See Section 12 for additional Ecological Information.		
Methods For Clean-Up:	Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.		
	. HANDLING AND STORAGE		
· · · · · · · · · · · · · · · · · · ·	. HANDLING AND STORAGE		
Handling:	Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.		
	Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable		

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### **Exposure Limits**

			AGCIH		OSHA Expo			
REPORTABLE COMPONENTS	CAS NUMBER	%WT	LV/TWA PPM	TV PPM	NA MG/M3	S1 PPM	TEL MG/M3	Vapor Pressure mm Hg @20° C
Limestone	1317-65-3	16.23	-	-	15	-	-	-
Titanium Dioxide	13463-67-7	11.70	10	-	10	-	-	-
Eye/Face Protection:	Saf	ety glasse	s with side	-shield	S.			
Skin Protection	Pro	tective glo	ves and im	npervio	us clothin	g.		
Respiratory Protection	In case of insufficient ventilation wear suitable respiratory equipment. When sanding or abrading the dried paint film, wear a dust / mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive material itself.							
Engineering Measures:	Ens	sure adequ	uate ventila	ition, es	specially i	n confin	ed areas	
Hygiene Measures:			with skin, clothing b	-		-		vash ter handling.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odor Odor Threshold pH Freezing Point (°F)

Product Name: V-PRO 5000 FLAT Product Code: .5100 Liquid Little or no odor No information available No information available 32 °F

Vista Paint Corporation

Page 3 of 7

**Boiling Point (°F)** Flash Point (°F) **Flash Point Method Evaporation Rate** Flammability (solid, gas) **Upper Explosion Limit** Lower Explosion Limit **Vapor Pressure** Vapor Density Density (lbs./gal) **Specific Gravity** Solubility Water Solubility Partition Coefficient (n-octanol/water) Autoignition Temperature (°F) **Decomposition Temperature (°F)** Viscosity (cps) Wt. % Solids Vol. % Solids Wt. % Volatiles Vol. % Volatiles **Coating VOC Material VOC** 

212 °F Not applicable Not applicable No information available Not applicable Not applicable Not applicable No information available No information available 11.50 1.38 No information available 57.60 41.50 42.40 58.50 0.41 g/l 0.17 g/l

### **10. STABILITY AND REACTIVITY**

Reactivity	Not Applicable
Chemical Stability	Stable under normal conditions.
Possibility Of Hazardous Reactions	None under normal conditions of use.
Conditions To Avoid	Prevent from freezing
Incompatible Materials	No materials to be especially mentioned.
Hazardous Decomposition Products	None under normal use.

### **11. TOXICOLOGICAL INFORMATION**

Inhalation	May cause irritation of respiratory tract.
Skin contact	Substance may cause slight skin irritation. Prolonged or repeated contact may dry skin and cause irritation.
Eye contact	May cause slight irritation.
Symptoms	No information available
Acute Toxicity:	No information available
Principal Routes of Exposure:	Eye contact, skin contact and inhalation.

Product Name: V-PRO 5000 FLAT Product Code: .5100 Vista Paint Corporation

Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Sensitization:	No information available
Neurological Effects	No information available.
Mutagenic Effects	No information available.
Reproductive Effects	No information available.
Developmental Effects	No information available.
Target Organ Effects	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Other adverse effects	No information available.
Aspiration Hazard	No information available
Carcinogenicity	No information available

### **12. ECOLOGICAL INFORMATION**

Ecotoxicity Effects	The environmental impact of this product has not been fully investigated.
Acute Toxicity to Fish	No information available
Acute Toxicity to Aquatic Invertebrates	No information available
Acute Toxicity to Aquatic Plants	No information available
Persistence / Degradability	No information available
Bioaccumulation / Accumulation	No information available
Mobility in Environmental Media	No information available
Ozone	No information available

### **13. DISPOSAL CONSIDERATIONS**

Waste Disposal Method

Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

Product Name: V-PRO 5000 FLAT Product Code: .5100 Vista Paint Corporation

## **14. TRANSPORT INFORMATION**

DOT	Not regulated
ICAO / IATA	Not regulated
IMDG / IMO	Not regulated

### **15. REGULATORY INFORMATION**

#### International Inventories

TSCA: United States	Yes - All components are listed or exempt.
DSL: Canada	Yes - All components are listed or exempt.

#### Federal Regulations

#### SARA 311/312 hazardous categorization

Please refer to Section 2 of the SDS for the appropriate EPCRA 311/312 hazard categories.

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). If listed in the table below, this product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name None CAS Number None

#### Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

Unless listed below, this product does not contain HAPs at 1% or 0.1% or greater. Refer to Section 3 for HAP weight percentage:

Chemical Name None CAS Number None

### State Regulations

#### **California Proposition 65**

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm at levels less than required for reporting (<0.1%) unless listed in Section 3.

16. OTHER INFORMATION					
<u>HMIS</u>	Health: 1*	Flammability: 0	Reactivity: 0	PPE: X	
<u>NFPA</u> :	Health: 1	Flammability: 0	Instability: 0		
Prepared ByVista Paint Constraint2020 East OraFullerton, CA(714) 680-380		ngethorpe Avenue 92831			
Product Name: Product Code:	V-PRO 5000 FLAT Vista Paint Corporation 5100		Page 6 of 7		

Print Date:	07/05/2023
SDS Revision Date:	03/16/2022
Revision Summary:	Formulation change

Disclaimer

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, provincial, and local laws and regulations.

Form Date: 2021-04-01

**END OF SAFETY DATA SHEET**