vista paint

5100

Zero* V.O.C., Low Odor Interior Latex Flat Architectural Coating - Premium

Description

V-PRO 5000 (5100 Flat) is a zero* VOC, interior latex flat for use on primed walls and ceilings including masonry, plaster, concrete, acoustic, wood and metal surfaces. This product offers excellent washability, high scrubbability and minimizes wall imperfections. **NOTE:** This product contains ingredients which resist the growth of mircrobes on the surface of the paint film.

Recommended Uses

Designed for commercial and institutional projects where a durable high scrub flat finish is required on new interior drywall, plaster, masonry, concrete, block, tilt-ups and acoustic surfaces.

Colors

Tintable White Bases: A, D & P

Packaging

One and five gallon containers

Finish

Flat, sheen @ 85° = 1.8 - 2.2%

Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming.

Primer

Masonry / Concrete: V-PRO 5001 Primer
Drywall (New): V-PRO 5001 Primer
V-PRO 5001 Primer
4000 Uniprime

8000 Carefree Prime-ZALL

Wood: 4000 Uniprime

8000 Carefree Prime-ZALL

Metal: 9600 Protec Metal Prime

Glossy Surfaces: 4000 Uniprime

<u>Application</u>

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Light overspray can be cleaned up with water even after drying. Clean tools and equipment with soap and water.

Drying Time

Touch: 1 hour Recoat: 4 hours

Coverage

Up to 400 square feet per gallon, depending on porosity and texture of the surface.

Mil Thickness

Wet = 4.4 Dry = 1.8

Thinning

Use at package consistency. If thinning is required, use water sparingly.

Composition

Titanium Dioxide	11.7%
Extenders	29.1%
TOTAL PIGMENT	40.8%

 Latex Resin
 13.5%

 Additives
 4.5%

 Water
 41.2%

 TOTAL VEHICLE
 59.2%

Weights & Measurements +/-3.0%

Solids by Volume: 41.1%
Solids by Weight: 57.4%
VOC: <2 g/l
Weight Per Gal: 11.5 lbs.
Viscosity: 96 - 102 KU

Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings.

LEED - complies with LEEDv4

CDPH Section 01350 - Standard Method V1.2 2017

MPI - #53 and #143

*NOTE: Zero VOC is defined as no VOC containing solvents added in the manufacturing process of this product. Slight traces of VOC are present in additives used in manufacturing. This product has less than half the allowable VOC of the SCAQMD Super Compliant Coatings category.

*NOTE: This product complies with the Super Compliant Coatings category under SCAQMD definitions.



Products bearing this logo are Non-EG Certified. Ethylene Glycol (EG), is listed as a toxic air contaminant and hazardous pollutant. EG is a solvent used in some water-based paints. Vista Paint has replaced EG with non-toxic alternative solvents. Any Vista Paint product with this logo is formulated without EG (Non-EG).



Vista Paint is the industry leader when it comes to relying on renewable energy. At Vista Paint, our products are manufactured using 100% solar energy.

12.2023

