

Biketrac Kote is a coating designed for bicycle lanes on asphalt and concrete roads. Biketrac Kote is a cost effective, high definition, two-component high build acrylic/epoxy hybrid coating manufactured in Bicycle Safety Green. This new and innovative chemistry offers fast drying, extreme wear & tear resistance, and supreme durability. Biketrac Kote is environmentally responsible, has better workability than older technologies such as standard two components coatings, and is a viable alternative to thermoplastic markings.

455
GREEN



Recommended Uses

Asphalt, concrete, and any other surfaces that may be used in marking of the roads and pavements.

Drying time (Time closed to traffic)

Thermoplastic (< 30 mins.)	MMA/Cold Plastic (~ 30 mins. - 1hr.)	Biketrac Kote (~ 1 - 2 hrs.)	2K 100% Epoxy (>3 hrs.)
-------------------------------	---	---------------------------------	----------------------------


Great Wear Resistance Shown by Lab Accelerated Tests

- Wheels turning at 60 rpm
- Load of 100 lbs. (tire pressure 50 psi)
- Tire shore hardness 65 +/- 5
- Continuous water wetting
- Friction and color measurement at interval of 0, 50K, 100K and 150K cycles

Three-Wheel Polishing Device



Biketrac Kote after 150K cycles



Conventional Traffic Paint after 50K cycles





Application

Pre-mix part A and part B by hand stirring for 2 - 3 minutes or a low-speed drill mixer can be used. Make sure part A and part B are thoroughly mixed. Spray application is recommended. Depending on width of the lane a spray machine with 2, or 3 spray heads can be used. Recycled glass aggregate, can be applied over Biketrac Kote at time of application to create a durable non-skid surface.


Painting Made Easy

- Fast, safe and low cost of application
- Long pot life [up to 12 hours]
- Fast drying



Typical Technologies for Green Bike Lanes

	Biketrac Kote	1K WB Acrylic	MMA/Cold Plastic	Thermoplastic	2K 100% Epoxy
Installed Price	\$4/sq ft	\$2/sq ft	\$11/sq ft	\$10-14/sq ft	\$8-11/sq ft
Pros	Low Cost, Easy Handling, Long Pot Life, Supreme Durability, Low Odor	Low Cost, Easy Handling, No Pot Life	Durable, Fast Drying Time	Durable, Short Open-to-traffic Time	Durable, Less Odor than MMA
Cons	None	Limited Durability	High Cost of Installation, Very Short Pot-Life, Odor	High Cost of Installation, Special Heating Equipment, Primer Might be Required	High Cost of Installation, Short Pot-Life, Long Drying Time



Visit Our Website & Follow Us On Social Media!

www.vistapaint.com

