

### Interior / Exterior Quicky Dry Primer Architectural Coating - Premium Plus

6600 AquaLac Waterborne Lacquer Undercoat Interior / Exterior Quicky Dry Primer

#### Description

AquaLac is a premium plus water-based quick dry lacquer primer, which offers excellent sanding properties, tanning resistance and minimum grain raising. AquaLac is designed for new or refinished projects over wood, drywall, paneling, hardboard and many other interior surfaces. This product offers excellent adhesion and enamel hold out.

#### Recommended Uses

Drywall, concrete, hardboard, wood, cabinets and interior / exterior doors & jambs.

#### Colors

White

#### Packaging

One and five gallon containers

#### Finish

Flat

#### Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings.

#### Primer

Masonry / Concrete / Block: 4600 Uniprime II

#### Application

Brush, roll or spray. A small amount of water (up to 5 oz. per gallon) will increase open time for brush or roll application. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

#### Drying Time

Sand After: 2 hours  
Top Coat After: 8 hours

#### Coverage

Up to 400 square feet per gallon, depending on porosity and texture of the surface.

#### Mil Thickness

Wet = 3.5                      Dry = 1.5

#### Thinning

If thinning is required, use water sparingly.

#### Composition

Titanium Dioxide	8.4%
Extenders	35.0%
<b>TOTAL PIGMENT</b>	<b>43.4%</b>
Acrylic Resin	19.3%
Additives	8.6%
Water	28.7%
<b>TOTAL VEHICLE</b>	<b>56.6%</b>

Weights & Measurements +/-3.0%

Solids by Volume:	42.9%
Solids by Weight:	59.9%
VOC:	<5 g/l
Weight Per Gal:	12.0 lbs.
Viscosity:	78 - 82 KU

#### Conformance

**SCAQMD** - complies with Rule 1113, Architectural Coatings.

**LEED** - complies with LEEDv4

**CDPH Section 01350** - Standard Method V1.2 2017

**MPI** - #39

\*NOTE: This product complies with the Super Compliant Coatings category under SCAQMD definitions.



Products bearing this logo are Non-EG Certified. Ethylene Glycol (EG), is listed as a toxic air contaminant and hazardous pollutant. EG is a solvent used in some water-based paints. Vista Paint has replaced EG with non-toxic alternative solvents. Any Vista Paint product with this logo is formulated without EG (Non-EG).



Vista Paint is the industry leader when it comes to relying on renewable energy. At Vista Paint, our products are manufactured using 100% solar energy.

12.2023

**DISCLAIMER:** To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

