

Interior Zero* V.O.C, Low Odor Primer
Architectural Coating - Premium

Description

Acriglo Primer is a premium low odor, zero* VOC interior primer. Provides superior adhesion and an excellent base for all Acriglo finishes. Excellent for use in hospitals, hotels/motels, schools, offices, homes and occupied areas with minimal disruption. **NOTE:** This product contains ingredients which resist the growth of microbes on the surface of the paint film.

Recommended Uses

New and previously painted drywall, concrete, plaster, masonry and wood.

Colors

White

Packaging

One and five gallon containers

Finish

Flat

Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Smooth wood and glossy or slick surfaces must be scuff sanded prior to application of paint coatings.

Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Light overspray can be cleaned up with water even after drying. Clean tools and equipment with soap and water.

Drying Time

Touch: 45 minutes
Recoat: 6 hours

Coverage

Up to 500 square feet per gallon, depending on porosity and texture of the surface.

Mil Thickness

Wet = 3.2 Dry = 1.2

Thinning

Use at package consistency. If thinning is required, use water sparingly.

Composition

Titanium Dioxide	8.8%
Extenders	23.2%
TOTAL PIGMENT	32.0%
PVA Resin	16.2%
Additives	4.1%
Water	47.7%
TOTAL VEHICLE	68.0%

Weights & Measurements +/-3.0%

Solids by Volume:	37.0%
Solids by Weight:	53.3%
VOC:	<3 g/l
Weight Per Gal:	11.2 lbs.
Viscosity:	94 - 96 KU

Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings.

LEED - complies with LEEDv4

CDPH Section 01350 - Standard Method V1.2 2017

MPI - #50, 149

EPA Test Method 24 - Yes

*NOTE: Zero VOC is defined as no VOC containing solvents added in the manufacturing process of this product. Slight traces of VOC are present in additives used in manufacturing. This product has less than half the allowable VOC of the SCAQMD Super Compliant Coatings category.

*NOTE: This product complies with the Super Compliant Coatings category under SCAQMD definitions.



Products bearing this logo are Non-EG Certified. Ethylene Glycol (EG), is listed as a toxic air contaminant and hazardous pollutant. EG is a solvent used in some water-based paints. Vista Paint has replaced EG with non-toxic alternative solvents. Any Vista Paint product with this logo is formulated without EG (Non-EG).



Vista Paint is the industry leader when it comes to relying on renewable energy. At Vista Paint, our products are manufactured using 100% solar energy.

12.2023

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

