Coverall Semi-Gloss

7400

Interior Vinyl Acrylic Enamel Finish

Architectural Coating - Quality

Description

Coverall Semi-Gloss is a quality interior vinyl acrylic enamel which provides excellent scrubbability and washability. For use on new or previously painted drywall, plaster and wood surfaces. Excellent choice for commercial, institutional, new home construction (walls and trim) and property management projects.

Recommended Uses

Properly primed new and existing interior drywall, plaster, concrete, masonry and wood. Not recommended for wood cabinets. For a block-resistant enamel, use Care-free Semi-Gloss.

Colors

Stock Colors: 23 Swiss Coffee
32 Shell White
33 Off White
60 Indian White

White - P and custom pastel colors to order

Packaging

One and five gallon containers

Finish

Semi-Gloss, sheen @ 60° = 58.0 - 64.0%

Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming.

Primer

Drywall (New):	1100 Hi-Build Sealer
Drywall (Existing):	4000 Uniprime
Concrete / Masonry:	4600 Uniprime II
Wood:	188 Acrylic Primer
	6600 AquaLac

Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

Drying Time

Touch:	2 hours
Recoat:	4 - 6 hours

Coverage

Up to 400 square feet per gallon, depending on porosity and texture of the surface.

Mil Thickness

Wet = 3.8 Dry = 1.3

Thinning

Use at package consistency. If thinning is required, use water sparingly.

Composition

Titanium Dioxide	20.6%
Extenders	3.9%
TOTAL PIGMENT	**24.5%**
Resin	23.5%
Additives	5.1%
Water	46.9%
TOTAL VEHICLE	**75.5%**

Weights & Measurements +/-3.0%

Solids by Volume:	33.8%
Solids by Weight:	46.2%
VOC:	46 g/l
Weight Per Gal:	10.2 lbs.
Viscosity:	96 - 104 KU

Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings.

Products bearing this logo are Non-EG Certified. Ethylene Glycol (EG), is listed as a toxic air contaminant and hazardous pollutant. EG is a solvent used in some water-based paints. Vista Paint has replaced EG with non-toxic alternative solvents. Any Vista Paint product with this logo is formulated without EG (Non-EG).

Vista Paint is the industry leader when it comes to relying on renewable energy. At Vista Paint, our products are manufactured using 100% solar energy.

12.2023

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

Vista Paint Corporation | 2020 E. Orangethrope Ave. Fullerton CA 92831
www.vistapaint.com

7400 Coverall Semi-Gloss Interior Vinyl Acrylic Enamel Finish