# Acriglo Eggshell

## Interior/Exterior Zero\* V.O.C., 100% Acrylic Enamel Finish

Architectural Coating - Premium

#### **Description**

Acriglo Eggshell is a premium zero\* VOC 100% acrylic for interior/exterior surfaces. This product provides good block resistance, durability, adhesion and mildew resistance. Low odor makes Acriglo Eggshell suitable for institutional, commercial and residential applications. **NOTE:** This product contains ingredients which resist the growth of mircrobes on the surface of the paint film.

vista paint

## Recommended Uses

Properly primed drywall, concrete, masonry, wood and metal.

#### **Colors**

White and custom colors Bases: D, & P

#### Packaging

One and five gallon containers

#### **Finish**

Eggshell, sheen at 60° = 18.0 - 20.0%

### Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Smooth Wood and glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming.

#### Primer

Drywall (New): Drywall (Existing): Concrete/Masonry: Wood (Exterior): Wood (Interior): Ferrous Metal:

4000 Uniprime 4600 Uniprime II 4200 Terminator II 4000 Uniprime 9600 Protec Metal Prime White 9610 Protec Metal Prime Red Oxide 4800 Metal Pro Primer White 4810 Metal Pro Primer Red Oxide

1100 Hi Build Sealer

#### **Application**

Non-Ferrous:

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

#### **Drying Time**

Touch:	2 hours
Recoat:	8 hours

## <u>Coverage</u>

Up to 398 square feet per gallon, depending on porosity and texture of the surface.

## Mil Thickness

Wet = 4.3

\_\_\_\_ Dry = 1.5

Diy =

#### <u>Thinning</u>

Use at package consistency. If thinning is required, use water sparingly.

Com	position

Titanium Dioxide	17.2%
Extenders	10.7%
TOTAL PIGMENT	27.9%
Resin	21.7%
Additives	6.1%
Water	44.3%
TOTAL VEHICLE	72.1%

Weights & Measurements +/-3.0%

Solids by Volume:	35.1%
Solids by Weight:	48.0%
VOC:	<2 g/l
Weight Per Gal:	10.4 lbs.
Viscosity:	92 - 96 KU

#### Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings. CDPH Section 01359 - Standard Method V1.2 2017 MPI - #143

\*NOTE: Zero VOC is defined as no VOC containing solvents added in the manufacturing process of this product. Slight traces of VOC are present in additives used in manufacturing. This product has less than half the allowable VOC of the SCAQMD Super Compliant Coatings category.

\*NOTE: This product complies with the Super Compliant Coatings category under SCAQMD definitions.



DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior

Products bearing this logo are Non-EG Certified. Ethylene Glycol (EG), is listed as a toxic air contaminant and hazardous pollutant. EG is a solvent used in some water-based paints. Vista Paint has replaced EG with non-toxic alternative solvents. Any Vista Paint product with this logo is formulated without EG (Non-EG).

Vista Paint is the industry leader when it comes to relying on renewable energy. At Vista Paint, our products are manufactured using 100% solar energy.



notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.