

Interior / Exterior 100% Acrylic Finish  
Architectural Coating - Premium Plus

### Description

Carefree Eggshell is a premium plus 100% acrylic eggshell enamel for interior and exterior surfaces. This top-of-the-line enamel provides block resistance with excellent scrubability and durability. Carefree Eggshell finish exhibits exceptional stain and dirt resistance with excellent hide and adhesion. Carefree can be used in areas where oil based products were previously required. Excellent choice for use on commercial, residential, institutional or custom painting projects. **NOTE:** This product contains ingredients which resist the growth of microbes on the surface of the paint film.

### Recommended Uses

Properly primed drywall, concrete, masonry, wood and metal.

### Colors

White, stock colors and custom colors to order

Bases: A, D, H, & M

### Packaging

Quarts, one and five gallon containers

### Finish

Eggshell, sheen at 60° = 14.0 - 18.0%

### Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Glossy or slick surfaces must be scuff sanded prior to application of paint coatings and may require priming.

### Primer

Drywall (New):	1100 Hi-Build Sealer 8000 Carefree Prime-ZALL
Drywall (Existing):	4000 Uniprime 8000 Carefree Prime-ZALL
Concrete/Masonry:	4600 Uniprime II 8000 Carefree Prime-ZALL 8600 Polytec Primer
Wood (Interior):	6600 AquaLac Undercoat 8000 Carefree Prime-ZALL 8600 Polytec Primer
Wood (Exterior):	4200 Terminator II 8000 Carefree Prime-ZALL 8600 Polytec Primer
Metal Non-Galvanized:	8600 Polytec Primer 9600 Protec Metal Prime
Metal Galvanized:	8600 Polytec Primer 4800 Metal Pro Primer
Aluminum:	8600 Polytec Primer

### Application

Brush, roll or spray. Ambient and surface temperatures must be above 50°F and relative humidity below 80%. Clean tools and equipment with soap and water.

### Drying Time

Touch:	1 hour
Recoat:	4 hours

### Coverage

Up to 400 square feet per gallon, depending on porosity and texture of the surface.

### Thickness

Wet = 4.3 mil	Dry = 1.5 mil
---------------	---------------

### Thinning

Use at package consistency. If thinning is required, use water sparingly.

### Composition

Titanium Dioxide	17.2%
Extenders	10.4%
<b>TOTAL PIGMENT</b>	<b>27.6%</b>
Acrylic Resin	21.3%
Additives	8.5%
Water	42.6%
<b>TOTAL VEHICLE</b>	<b>72.4%</b>

Weights & Measurements +/-3.0%

Solids by Volume:	36.0%
Solids by Weight:	50.3%
VOC:	43 g/l
Weight Per Gal:	10.8 lbs.
Viscosity:	96 - 100 KU

### Conformance

**SCAQMD** - complies with Rule 1113, Architectural Coatings.

**LEED** - complies with LEEDv4

**CDPH Section 01350** - Standard Method V1.2 2017

**MPI** - #15, #52, #139, #151, #161



Products bearing this logo are Non-EG Certified. Ethylene Glycol (EG), is listed as a toxic air contaminant and hazardous pollutant. EG is a solvent used in some water-based paints. Vista Paint has replaced EG with non-toxic alternative solvents. Any Vista Paint product with this logo is formulated without EG (Non-EG).



Vista Paint is the industry leader when it comes to relying on renewable energy. At Vista Paint, our products are manufactured using 100% solar energy.

Last Updated 04.2024

**DISCLAIMER:** To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.

