

Interior Primer and Undercoat Architectural Coating - Production

Description

A production acrylic co-polymer interior primer and undercoater. VP20 Interior Wood Primer offers excellent hold-out, leveling and bridging characteristics. Designed to sand easily.

Recommended Uses

New wood, hardboard and most previously painted surfaces. Not recommended for redwood, cedar and other woods prone to extractive bleeding. May be top coated with waterbase products.

Colors

White

Packaging

Five gallon containers

Surface Preparation

Surfaces must be clean, dry and free from all contaminants that may impair adhesion. Smooth wood and glossy or slick surfaces must be scuff sanded prior to application of paint coatings.

Application

Brush, roll or spray. Ambient and surface temperatures must be above 55°F and relative humidity below 80%. Clean tools and equipment with soap and water.

Drying Time

Touch: 1 hour
Recoat: 4 hours

Coverage

Up to 450 square feet per gallon, depending on porosity and texture of the surface.

Mil Thickness

Wet = 4.0 Dry = 1.5

Thinning

Use at package consistency. If thinning is required, use water sparingly.

Composition

Titanium Dioxide	11.0%
Extenders	30.6%
TOTAL PIGMENT	41.6%

Solid Resin	16.7%
Additives	1.3%
Water	40.4%
TOTAL VEHICLE	58.4%

Weights & Measurements +/-3.0%

Solids by Volume:	39.0%
Solids by Weight:	57.5%
VOC:	38.48 g/l
Weight Per Gal:	11.8 lbs.
Viscosity:	91 - 95 KU

Conformance

SCAQMD - complies with Rule 1113, Architectural Coatings.



Products bearing this logo are Non-EG Certified. Ethylene Glycol (EG), is listed as a toxic air contaminant and hazardous pollutant. EG is a solvent used in some water-based paints. Vista Paint has replaced EG with non-toxic alternative solvents. Any Vista Paint product with this logo is formulated without EG (Non-EG).



Vista Paint is the industry leader when it comes to relying on renewable energy. At Vista Paint, our products are manufactured using 100% solar energy.

12.2023

DISCLAIMER: To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance and offered in good faith. All technical information is subject to change without prior notice. This product is guaranteed to give satisfactory performance if applied and used in accordance with the label instructions. Any liability shall be limited to a refund of the purchase price, or replacement of this product. This warranty does not include labor or cost of labor for the application of any coating. All express and all implied warranties are hereby disclaimed and excluded including all implied warranties of fitness for a particular use and merchantability. Final determination of the suitability of product or intended use is the sole responsibility of the user. Additional information may be obtained from your local sales representative.